

### Description

ASC A-1000 is a multi-purpose sealant used for bonding and sealing a range of construction materials. ASC A-1000 is a moisture cure sealant, that is solvent-free and low VOC. ASC A-1000 is an elastomeric based waterproofing seal with flexibility and superior adhesion to most construction materials, including skylights, metal flashing, copings, and HVAC surfaces.

ASC A-1000 is used as a waterproofing seal to most roofing materials, masonry, wood, glass, aluminum and foam. ASC A-1000 can also be used as a waterproofing complement for wall application and can be used as a termination sealant as well as to fill and repair horizontal and vertical voids of concrete and masonry substrates that do not exceed 13 mm (1/2") in width.

Read and follow directions carefully. Refer to Material Safety Data Sheet for proper handling.

### Preparation

Surfaces must be cleaned, dried, and free of moisture on and beneath the surface. Remove dust, dirt, oil, paint, loose granules, mildew and any other foreign contaminants. Rusted metal should be cleaned with a wire brush. Do not use petroleum solvents such as mineral spirits or xylene.

Acceptance of the substrate is the sole decision of the owner or appointed representative.

### Application

For exterior use only. Protective clothing and eyewear should be used during application of this product.

Apply ASC A-1000 with caulking guns. Initial curing time varies from 30 minutes to an hour with complete cure after 24 hours depending on temperature and relative humidity.

Test and evaluate to ensure adequate adhesion. Tool the sealant within 15 minutes of application.

Application temperatures: above 0°C (32°F)

Service temperatures: -40°C to 93°C (-40°F to 200°F)

### Cleanup

Uncured material and tools can be cleaned using alcohol base cleaning product.

### Precautions

DO NOT STORE AT TEMPERATURES BELOW 50°F (10°C) OR ABOVE 120°F (49°C). DO NOT ALLOW TO FREEZE. DO NOT APPLY WHEN HEAVY DEW OR RAIN IS EXPECTED WITHIN 24 HOURS. DO NOT THIN.

Drying time may vary depending upon wet film thickness, temperature, humidity and air movement.

### CAUTION

KEEP OUT OF REACH OF CHILDREN. Close container after each use. HARMFUL OR FATAL IF SWALLOWED. EYE, SKIN, AND RESPIRATORY IRRITANT. USE WITH ADEQUATE VENTILATION. If swallowed do not induce vomiting. Call physician immediately. In case of eye contact- flush with large amounts of room temperature water for 15 minutes, skin contact- wash thoroughly with soap and water. Irregular or stopped breathing administer oxygen, give artificial respiration. Get immediate medical attention. Avoid prolonged breathing of vapor or spray mist.

CALIF PROP 65- CHEMICAL WARNING (CALIFORNIA HEALTH AND SAFETY CODE #25249.5 ET SEQ) WARNING: This product contains chemicals known to the State of California to cause cancer, birth defects or reproductive harm. Use proper protection and adequate ventilation when using product.

For Further information and advice regarding transportation, handling, storage, and disposal of chemical products, users should refer to the actual Material Safety Data Sheet containing physical, ecological, toxicological, and other safety related data. It is highly recommended to read the actual Material Safety Data Sheet before using the product.

### WARRANTY AND DISCLAIMER

ASC Building Materials warrants to the original purchaser that this product is free from any manufacturing defects that will materially affect the products performance for a period of one year. In the event there is a failure associated with a manufacturing defect of this product, ASC Building Materials shall, at its own discretion, provide the appropriate replacement product(s) or pay for the cost of the defective product only. There is no warranty for labor or installation costs of any kind. NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. AMERICAN STANDARD COATINGS SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. Contact ASC Building Materials prior to ordering for the most recent and up to date data sheet. For additional limited warranty and disclaimer information contact the ASC Building Materials corporate office at 562-777-8200.

See SDS, Technical Data Guide and Warranty for complete details at [www.ASC-BM.com](http://www.ASC-BM.com)



## ASC A-1000

### All Purpose Sealant & Adhesive

Available Colors:  
White / Gray / Tan / Black

Packaging:  
10.5 oz tube